

LESONAL®

2K OPTIC CLEAR RTS



**CLEAR BENEFITS
FOR THE BODYSHOP**

GREAT FINISH. FAST.

WIDEN YOUR OFFER AND INCREASE PRODUCTIVITY

Strengthen the offer of your bodyshop and enhance customer satisfaction with Lesonal 2K Optic Clear RTS, the innovative headlight clearcoat refurbishment solution. It restores the original clearcoat on polycarbonate headlights as clear as new – ensuring drivers' visibility and safety and avoiding the high cost of a replacement.

As it is aerosol-based, there is no need for mixing, resulting in greater productivity, in line with the Lesonal pledge to provide the fastest high-quality system and most efficient refinishing process.

EFFICIENT PROCESS

There's no need for mixing with 2K Optic Clear RTS. Supplied as an aerosol, it can be applied direct to a sanded substrate with no additional adhesion primer required – eliminating the time and material needed. A single coat is all that's needed.

INCREASED SATISFACTION

2K Optic Clear RTS enables you to widen the offering of your bodyshop and provide a new solution to customers by avoiding the cost of replacement headlights - increasing their satisfaction, building loyalty and enhancing your bodyshop's reputation.

CONSISTENT RESULTS

Effective headlight clearcoat refurbishment, with no compromise on quality. The great adhesion properties of 2K Optic Clear RTS offer a universal solution for use on all OEM headlights.

FEATURES	BENEFITS
True-to-the-original result, with excellent adhesion	No costly headlight replacement Restoration of light output
Simple system configuration	No adhesion agent necessary Investment in just one product Fastest repair process Simple handling
Application in just one coat	Saves material Saves time Faster process
Available in aerosol	No mixing required

EFFICIENT

A single coat is sufficient

CONSISTENT

Universal solution for all OEM headlights

INNOVATIVE

Widen the offering of your bodyshop



QUICK REFERENCE GUIDE

2K OPTIC CLEAR RTS

Cleaning



Clean with Lesonal Degreaser WB 200

Sanding



P320 – P400 – P500 – P600 – P1000 – P1500 – P3000 wet

*Ensure recommended sanding steps are followed

Cleaning




Clean with Lesonal Degreaser WB 200

Preparation



Shake well



Place button on pin at bottom



Push button once to activate

Application



Shake for 2 mins




Distance approx. 10 cm



1 coat

Flash-off



Before curing:
5-10 mins at 20°C



After use, invert aerosol to clear nozzle

Drying time



7 hrs at 20°C
30 mins at 60°C

Protection



Use suitable respiratory protection
Akzo Nobel Car Refinishes recommends the use of fresh air supply respirator

To widen your bodyshop offer, visit www.lesonal.uk